

# NTM-710

## 6" Air-Tight Aluminum Cone Reflector

Type	
Project	
Catalog No.	
Notes	

### CONSTRUCTION

Precision spun 0.040 aluminum reflector to reduce aperture glare available in Black and White.

### MOUNTING

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Socket can be mounted directly to trim without bracket.

### COMPATIBLE LAMP / HOUSINGS

#### Line Voltage:

100W BR40/PAR38 Maximum (NHIC-17QAT; NHIC-17QNBAT; NHIC-17/100DWQA; NHR-26Q; NHRIC-17QAT; NHRIC-17QNBAT)  
150W BR40/PAR38 Maximum (NH-26Q; NH-26QNB; NHR-26Q);

### LISTINGS

· cULus Listed for Damp Location when used with compatible housing




### PRODUCT IMAGES AND DIMENSIONS



NTM-710BBAL



NTM-710WAL



## 6" Air-Tight Aluminum Cone Reflector

Catalog No.

NTM-710BBAL = 6" Black Air-Tight Aluminum Cone Reflector

NTM-710WAL = 6" White Air-Tight Aluminum Cone Reflector

## Compatible Housings

Catalog No.

NH-26Q = Non-IC New Construction / 150W max.

NH-26QNB = Non-IC New Construction; No bracket / 150W max.

NHIC-17/100DWQA = ICAT Double Wall New Construction / 100W max.

NHIC-17QAT = ICAT New Construction / 100W max.

NHIC-17QNBAT = ICAT New Construction; No bracket / 100W max.

NHR-26Q = Non-IC Remodel / 150W max.

NHRIC-17QAT = ICAT Remodel / 100W max.

Example: NTM-710WAL = 6" White Air-Tight Aluminum Cone Reflector