

NTS-5022

5" Front Loading Abalite Lens with Specular Clear Reflector

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun 0.050 aluminum high grade specular clear reflector with high grade abalite lens attached to trim. Easy lift and turn lens removal for re-lamping. Reflector includes two socket positions for optimum light control and output.
Note: Shallow housings must use lowest socket position.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

25W A19 Maximum (NHIC-501QAT; NHRIC-504QAT)

35W PAR30 Maximum (NHIC-501QAT; NHIC-527QAT; NHRIC-504QAT; NHRIC-527QAT)


60W A19 Maximum (NH-501Q; NHR-504Q)

LABELS AND LISTINGS

· cULus Listed for Wet Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



5" Front Loading Abalite Lens with Specular Clear Reflector

Catalog No. _____

NTS-5022W = 5" Front Loading Abalite Lens with Specular Clear Reflector and White Trim

Compatible Housings

Catalog No. _____

NH-5010 = 5" Non-IC New Construction Housing / 60W max

NHR-5040 = 5" Non-IC Remodel Housing / 60W max

NHIC-501QAT = 5" IC Air-Tight New Construction Housing / 35W max

NHRIC-504QAT = 5" IC Air-Tight Remodel Housing / 35W max

NHIC-527QAT = 5" IC Shallow Air-Tight New Construction Housing / 35W max

NHRIC-527QAT = 5" IC Shallow Air-Tight Remodel Housing / 35W max

Example: **NTS-5022W** = 5" Front Loading Abalite Lens with Specular Clear Reflector and White Trim