

NTS-714

6" Specular Reflector with White Plastic Ring

Type _____

Project _____

Catalog No. _____

Notes _____

CONSTRUCTION

Precision spun 0.050 aluminum high grade specular reflector and white plastic ring. Trim may also be used with custom combination of ring finishes.

MOUNTING

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Socket can be mounted directly to trim without bracket.

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

60W A19 Maximum (NH-26Q; NHIC-17/100DWQA; NHIC-17QAT; NHIC-17QNBAT; NHR-26Q; NHRIC-17QAT; NHRIC-17QNBAT)

75W BR/PAR30 Maximum (NHIC-17QAT; NHIC-17NBAT; NHRIC-17QAT; NHRIC-17QNBAT; NFBIC-6INCATA)

90W BR40/PAR38 Maximum (NFBIC-6INCATA)

100W BR40/PAR38 Maximum (NHIC-17/100DWQA)

150W BR40/PAR38 Maximum (NH-26Q; NHR-26Q);

LISTINGS


· cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



NTS-714C



6" Specular Reflector with White Plastic Ring

Catalog No. _____

NTS-714C = 6" Specular Clear Reflector with White Plastic Ring

Compatible Housings

Catalog No. _____

NH-26Q = Non-IC New Construction / 150W max.

NHIC-17/100DWQA = ICAT Double Wall New Construction / 100W max.

NHIC-17QAT = ICAT New Construction / 75W max.

NHIC-17QNBAT = ICAT New Construction; No bracket / 75W max.

NHR-26Q = Non-IC Remodel / 150W max.

NHRIC-17QAT = ICAT Remodel / 75W max.

NHRIC-17QNBAT = ICAT Remodel; No bracket / 75W max.

NFBIC-6INCATA = ICAT Fire Rated New Construction / 90W Max

Example: NTS-714C = 6" Specular Clear Reflector with White Plastic Ring