BNORA | NSPEC

Type


Proiect

Catalog No.

Lamp/Wattage

NL-3350 Adjustable Wall Wash with Reflector

TRIM DIMENSIONS



Trim OD: 3-5/8" Height: 1-5/8"

FEATURES

Trim

Precision spun 0.050 aluminum high grade reflector with half moon. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Trim ring available in metal, may also be used with custom combination of ring finishes.

Mounting

Trim includes three trim clips that securely mount trim in housing.

Compatible Housings

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

Lamp

Line Voltage

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

Low Voltage

IMPORTANT: DO NOT USE $\underline{\text{GLASS LENS}}$ (PROVIDED) WHEN ALREADY USING $\underline{\text{LAMP WITH GLASS COVER}}$

20W-50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series)

Labels and Listings

cULus Listed for Damp Location when used with compatible housing.

Compatible Housings

Item Number

NLR-3040AT

NLR-304AT/1EL

	NH-350AT	Non-IC Air-Tight New Const.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"			
F	NHIC-350AT	IC Air-Tight New Construction	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"			
	NHR-354AT	Non-IC Air-Tight Remodel	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"			
I	LOW VOLTAGE						
	NL-301QAT/20	Non-IC AT New Const., Mag.	20W MR16	W: 6-3/8" L: 16" H: 5-5/8"			
	NL-301QAT/37	Non-IC AT New Const., Mag.	37W MR16	W: 6-3/8" L: 16" H: 5-5/8"			
4	NL-301QAT	Non-IC AT New Const., Mag.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"			
	NL-301AT/1EL	Non-IC AT New Const., Elec.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"			
	NLIC-301QAT/20	IC Air-Tight New Const., Mag.	20W MR16	W: 6-3/8" L: 16" H: 8-1/8"			
	NLIC-301QAT/37	IC Air-Tight New Const., Mag.	37W MR16	W: 6-3/8" L: 16" H: 8-1/8"			
	NLIC-301QAT	IC Air-Tight New Const., Mag.	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"			
	NLIC-301AT/1EL	IC Air-Tight New Const., Elec.	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"			
	NLR-304QAT/20	Non-IC Air-Tight Remodel, Mag.	20W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"			
	NLR-304QAT/37	Non-IC Air-Tight Remodel, Mag.	37W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"			

LINE VOLTAGE

Lamp

Dimensions

Installation Type

Non-IC Air-Tight Remodel, Mag.

Non-IC Air-Tight Remodel, Elec.

Adjustable	Wall	Wash	with	Reflec	tor

.

NL-3350B: Black Adjustable Wall Wash with Specular Black Reflector and Black Ring

NL-3350BZ: Bronze Adjustable Wall Wash with Bronze Reflector and Bronze Ring

NL-3350C: Chrome Adjustable Wall Wash with Specular Clear Reflector and Chrome Ring

NL-3350CO: Copper Adjustable Wall Wash with Copper Reflector and Copper Ring

NL-3350G: Gold Adjustable Wall Wash with Specular Gold Reflector and Gold Ring

NL-3350N: Natural Metal Adjustable Wall Wash with Natural Metal Reflector and Natural Metal Ring

NL-3350W: White Adjustable Wall Wash with Specular White Reflector and White Ring

50W MR16 W: 4-1/4" L: 11-1/4" H: 5-5/8"

50W MR16 W: 4-1/4" L: 11-1/4" H: 5-5/8"