

NT-40

6" BR40/PAR38 Open Metal Trim

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Metal trim with 5-1/8" open center.

Mounting: Trim includes two coil springs that clip and securely hold the trim into the housing when installed. Replacement coil springs are available (NRA-22).

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

100W BR40/PAR38 Max. (NHIC-17/100DWQA)


150W BR40/PAR38 Max. (NH-26Q; NH-27Q; NHR-26Q; NHR-27Q)

LABELS AND LISTINGS

* cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS



6" BR40/PAR38 Open Metal Trim

Catalog No. _____

NT-40 = 6" BR40/PAR38 White Open Metal Trim

Compatible Housings

Catalog No. _____

NH-26Q = Non-IC New Construction / 150W max

NHR-26Q = Non-IC Remodel / 150W max

NH-27Q = Shallow Non-IC New Construction / 150W max

NHR-27Q = Shallow Non-IC Remodel / 150W max

NHIC-17/100DWQA = IC Air-Tight Double Wall New Construction / 100W max

Example: **NT-40** = 6" BR40/PAR38 White Open Metal Trim