

RLM LED SHADES

8", 10" or 16" Diameter

A beautiful timeless aluminum spun shade fits many decors. The LED optics are deep set in the bowl for even distribution and visual comfort. A bright white reflective interior produces true 90+ CRI color. Shades are available in three sizes and multiple finishes.

FEATURES

- Over 80% energy savings when compared to incandescent
- 8", 10" or 16" diameter shades
- 1200lm, 2000lm, 2200lm, 2500lm, 3000lm or 3800lm output
- Field adjustable pendant cord or stem mounted
- 3000K, 3500K and 4000K @ 90+ CRI
- 120/277V input with Triac, ELV or 0-10V dimming
- Built-in LED driver allows for minimal canopy size
- Available in black, gun metal and white finishes
- 5-Year limited warranty
- ENERGY STAR® certified
- Can be used to comply with 2019 Title 24 - part 6 High Efficacy LED light source requirements
- cULus listed for Damp Location



| RLM LED SHADES | | | | | | |
|--|---|--|---|--|--|--|
| SHADE DIAMETER | MOUNTING | LUMENS / WATTAGE | COLOR TEMPERATURE | SHADE FINISH | DIMMING | STEM LENGTH |
| NRLM-8 = 8" NRLM-10 = 10" NRLM-16 = 16" | C = 8' Cable ST = Stem | 10 = 1200lm / 15W (8" only) 18 = 2200lm / 30W (8" only) 20 = 2000lm / 23W (10" only) 30 = 3000lm / 36W (10" only) 25 = 2500lm / 27W (16" only) 38 = 3800lm / 48W (16" only) | 30 = 3000K 35 = 3500K 40 = 4000K | BW = Black Outer / White Inner GMW = Gun Metal Outer / White Inner WW = White Outer / White Inner | LE4 = 120-277V input; Triac / ELV / 0-10V | /12 = 12" Stem /24 = 24" Stem /36 = 36" Stem /48 = 48" Stem /60 = 60" Stem /72 = 72" Stem /84 = 84" Stem /96 = 96" Stem |

Example: **NRLM-10C3035BWLE4** - 10" RLM LED Shade with 8' Cable, 3000lm / 36W, 3500K, Black Outer White Inner Finish