

## NEW PRODUCT ANNOUNCEMENT

# **FLIN SERIES** Thin LED Recessed Series

Thin, regressed LED recessed luminaire designed for easy installation in new construction or remodel applications, no housing is required. FLIN includes a quick connect that allows the junction box to easily disconnect and mount in the ceiling. Junction box measures under 2" for shallow plenum ceilings where access above the ceiling is limited. The regressed lens with sharp baffle cuts reduces aperture brightness.

## FEATURES

- · Regressed lens with baffle
- · Thin construction measures under 2" height
- · IC Air-Tight & wet location listed
- · Quick disconnect allows for easy installation
- $\cdot\,$  Up to 2350Im LED packages
- · 2700K, 3000K, 3500K, 4000K or 5000K at 90+ CRI
- · Triac or ELV dimming
- · 5-Year limited warranty
- · ENERGY STAR Certified
- Can be used to comply with 2016 Title 24 Part 6 high efficacy LED light source requirements



### FLIN LED RECESSED SERIES

Size / Lumens / Wattage	Color Temp	Finish	Voltage	
NFLIN-R407 = 4" Round / 800lm / 12W NFLIN-S407 = 4" Square / 750lm / 12W NFLIN-R610 = 6" Round / 1450lm / 16W NFLIN-S610 = 6" Square / 1150lm / 16W	<b>27</b> = 2700K <b>30</b> = 3000K <b>35</b> = 3500K <b>40</b> = 4000K	WW = White	<b>LE3</b> =120V input; Triac / ELV dimming	
NFLIN-R815 = 8" Round / 1900lm / 20W NFLIN-S815 = 8" Square / 1400lm / 20W	<b>30</b> = 3000K <b>35</b> = 3500K <b>40</b> = 4000K <b>50</b> = 5000K	-		
NFLIN-R822 = 8" Round / 2350lm / 33W NFLIN-S822 = 8" Square / 2350lm / 33W			LE4 =120/277V input; Triac / ELV dimming	

Example: NFLIN-R61030WWLE3 - 6" Round / 1450lm / 16W, 3000K, White

#### FRAME-IN KITS

Catalog No.

NFLIN-4R-F = 4" Flat Round Frame-In Kit
<b>NFLIN-4S-F</b> = 4" Flat Square Frame-In Kit
<b>NFLIN-6R-F</b> = 6" Flat Round Frame-In Kit
<b>NFLIN-6S-F</b> = 6" Flat Square Frame-In Kit
NFLIN-8R-F = 8" Flat Round Frame-In Kit
<b>NFLIN-8S-F</b> = 8" Flat Square Frame-In Kit





