

JOSH LED PUCK

12V LED Puck Light

Nora Lighting introduces Josh, a slim light disk LED system for accent, under cabinet, in- cabinet, niche, and jewelry cases, and other applications with limited space. These low-profile fixtures can be spaced together to provide excellent and even illumination on all surfaces. The Josh pucks do not produce diode image and can be recessed or surface mounted. Combined with ultra low-profile housing, Nora's light disk offers unique features and a great ease of installation. LED technology eliminates forward heat from the fixture, also no UV or infrared rays to harm artwork, retail displays or heat sensitive foods. Josh LED Puck produces more light than a traditional 20W xenon or halogen puck while consuming only 3.5W.



FEATURES

- 300 lumens / 3.5W
- Well suited for very small spaces: 0.6" deep with 2.72" diameter
- Recessed or Surface Mounted
- Easy installation
- Dimmable with dimmable power supply
- 12" to 48" extension cables accessory available
- 2700K, 3000K, 3500K or 4000K @ 90+CRI
- No flicker delay or warm up like compact fluorescent products
- No diode image
- No UV light or infrared wavelengths
- cULus Listed for Damp Location
- 5-Year Limited Warranty



JOSH LED PUCK		
SERIES	CCT	FINISH
NMP-LED	27 2700K	B Black
	30 3000K	BZ Bronze
	35 3500K	BN Brushed Nickel
	40 4000K	W White

Example: **NMP-LED30BZ** - 12V Josh LED Puck, 3000K, Bronze finish



JOSH LED PUCK LIGHT DRIVERS & ACCESSORIES



6-Port Power Line Interconnect

NMPA-6P-24B	Black
NMPA-6P-24W	White

Terminal block connects up to six LED Josh Puck lights to a Nora driver. Includes 24" cord with RCA jack.



Extension Cable

NMPA-EW-12	12" Cable
NMPA-EW-24	24" Cable
NMPA-EW-36	36" Cable
NMPA-EW-48	48" Cable

Finish: Black (B), White (W)


Used to extend the length of the cable from the puck to the terminal block. Linkable up to 110'.



2' Wire Raceway

NATL-422B	black
NATL-422W	white

Field-cutable plastic. Includes wire channel with double faced tape and cover.



In-Line Touch Dimmer

[NATL-518W](#)

72W max., no power fail memory, touch on/off and hold to dim.



In-Line Motion Sensor

[NAL-856W](#)

12' Max activation distance; 20 second auto off; 120° detection zone; Max Load 4A.



Direct Plug-In LED Driver

NAPK-524W/12	24W
NAPK-560W/12	60W

Voltage: 120V

Wattage: 24W or 60W

Dimming: Non-Dimmable

Cable Length:

4' cord & plug and 48" power line connector for NAPK-560W/12



Class II Hardwire LED Driver

NAPK-5030HW/12	30W
NAPK-5060HW/12	60W

Voltage: 120-240V/12V

Wattage: 30W or 60W

Dimming: Non-Dimmable

Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Regulator, MLV dimming

NMTD-40/12D	40W
NMTD-60/12D	60W

Voltage: 120-277V/12V

Wattage: 40W or 60W

Dimming: Magnetic Low Voltage

Regulator: Integral regulator for constant current and voltage

Includes: 10' Power Line Connector



Class II Hardwire LED Driver ELV dimming

NAPKED-5040HW	12V 35W
NAPKED-5060HW	12V 60W

Input Voltage: 120V

Dimming: Electronic Low Voltage

Includes: 10' Power Line Connector



Class II Hardwire LED Driver 0-10V dimming

NATL-5060-12-HWD10	60W
------------------------------------	-----

Voltage: 120-277V/12V

Wattage: 60W

Dimming: 0-10V

Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV dimming

NMT-244/12C2D1	4x60W
--------------------------------	-------

Input Voltage: 120V or 277V

Dimming: Magnetic Low Voltage

Wattage: (4) 60W

Includes: (4) 10' Power Line Connectors



Power Line Connector

NATL-10	10' Cable
NATL-30	30' Cable

For use with Class II drivers. Carries output from driver, requires power line cable.

5" Power Line Splitter

NATL-302W	5" Cable
---------------------------	----------



Low Voltage Splice Box

[NATL-415W](#)

Use to join low voltage lead to low voltage power line connector or interconnector.



16AWG In-Wall Rated Wire

NATL-W16-2-250	16AWG 250'
NATL-W16-2-20	16AWG 20'

16 AWG low voltage Class II two-conductor, in-wall rated wire.