NLCBC-651 Series

6" Cobalt Retrofit Reflectors

Source: 12W LED 750lm

Type Project Catalog No. Notes

PRODUCT DESCRIPTION

Cobalt retrofit series is cULus classified for use in existing IC or Non-IC housings manufactured by Nora and others. The 6" retrofit luminaires produces 750 lumen output at 90+ CRI. The Cobalt series integrates a Cree® COB family of LED arrays, giving bright spectacular light output and low power consumption. An obvious and smart choice for Green Energy efficient lighting in commercial and residential applications.

FEATURES

- · 750lm / 12W LED output
- · 3000K or 3500K @ 90+ CRI
- CREE® COB LED technology
 Integral dimmable driver
- Includes medium base socket adapter for easy retrofitting in 6" recessed housings
- 5-year limited warranty
- · ENERGY STAR certified
- · cULus classified for wet locations

SPECIFICATION

Reflector: Aluminum spun reflector with deep set diffused lens for excellent visual comfort while providing high lumen output. The deep reflector places the LED optics deeper, increasing the visual comfort and reduces board images when off.

Mounting: Two steel, spring mounting blades allow for easy and secure mounting in most 6" housings.

Retrofit: Cobalt retrofit series includes medium base screw-socket adapter (NRA-211SM) for retrofitting into existing medium base downlight housings. GU24 socket adapter is available for use with GU24 housings, must specify NRA-212SM.

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage: 750lm / 12W Color Temperature: 3000K or 3500K

CRI: 90+CRI

Operating Temp.: 0°C to 45°C ambient temperature

Dimming: Triac/ELV

<u>Click Here</u> or check complete dimmer list at

www.NoraLighting.com in the "Compatibility" page under

"Resources" tab

COMPATIBLE HOUSINGS

Cobalt retrofit reflectors are compatible with most 6" IC and Non-IC housings by Nora and others.

Fire Box

NFBIC-6LMRAT* ICAT Dedicated LED
NFBIC-6INCAT ICAT Line Voltage

New Construction

NHIC-27LMRAT* Shallow ICAT Dedicated LED
NHIC-6LMRAT* ICAT Dedicated LED
NHIC-6LMRAT/277* ICAT Dedicated LED, 277V

(includes step-down transformer)

NHICCP-6LMRAT* Chicago Plenum Dedicated LED
NHIC-270AT Shallow ICAT Line Voltage
NHIC-170AT ICAT Line Voltage
NH-260 Non-IC Line Voltage
NHIC-6624ATFL ICAT GU24

Remodel

NHRIC-27LMRAT* Shallow ICAT Dedicated LED
NHRIC-6LMRAT* ICAT Dedicated LED
NHRIC-270AT Shallow ICAT Line Voltage
NHRIC-170AT ICAT Line Voltage
NHR-260 Non-IC Line Voltage
NHRIC-6624ATFL ICAT GU24

* Nora Dedicated LED housings are cULus listed for use only with Nora LED Retrofits.

ACCESSORIES

NLCBC-6EYELID: Round eyelid used to convert round reflector or baffle to half moon wall wash trim. **NLCBC-60R:** Round oversize ring used to cover ceiling cut-outs up to 8-1/4".

LABELS AND LISTINGS

- · cULus classified for Wet Locations
- · ENERGY STAR certified
- <u>5-Year Limited Warranty</u>
- Can be used to comply with 2016 Title 24 part 6
 High Efficacy LED light source requirements













PRODUCT IMAGES & DIMENSIONS



NLCBC-651 Round Reflector BBL, WWL

6" Cobalt Retrofit Reflectors

Reflector Type Color Temp. / Finish

NLCBC-651 = Round Reflector 30BBL = 3000K, Black Reflector / Black Flange

35WWL = 3500K, White Reflector / White Flange

Optional Accessories Description

NLCBC-6EYELIDB = 6" Round Eyelid, Black

 ${f NLCBC-6EYELIDBZ}=6"$ Round Eyelid, Bronze

NLCBC-6EYELIDMPW = 6" Round Eyelid, Matte Powder White

 $\mbox{NLCBC-6EYELIDW} = 6$ " Round Eyelid, White

 $\mathbf{NLCBC\text{-}60R\text{-}B} = 6$ " Round Oversize Ring, Black

NLCBC-60R-BZ = 6" Round Oversize Ring, Bronze

 $\textbf{NLCBC-60R-MPW} = 6" \ \text{Round Oversize Ring, Matte Powder White}$

 $\textbf{NLCBC-60R-W} = 6 \mbox{"}$ Round Oversize Ring, White

NRA-211SM = Medium base screw-in socket (included)
NRA-212SM = Socket adapter for use with GU24 housings

Example: NLCBC-65130BBL = 6" Cobalt Retrofit Reflector, 750lm / 12W LED, 3000K, Black Reflector / Black Flange

