

NTLE-842

4' Track Pack with (3) 2200lm Aiden LED Track Heads

Source: 35W LED per head  
2200lm per head

Type
Project
Catalog No.
Notes

PRODUCT DESCRIPTION

Track pack comes complete and ready to install with mounting hardware and track heads. Components includes: (1) 4' single circuit track, (2) end caps, (1) floating canopy feed and (3) 2200lm Aiden LED track heads. The utilitarian style fits almost any design criteria.

FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- 2200lm / 35W LED output per head
- Each track head includes a spot (included) and flood (installed) optic
- Easily to longer lengths or additional track heads
- Perfect for multi family homes or apartments
- 5-Year Limited Warranty

CONSTRUCTION

**Track Extruction:** 0.030 die cast aluminum construction with 0.045 PVC insulators holding 12-gauge flat conductor wiring. Polarity groove is located on face of track to indicate location of grounding conductor.

**Track Head:** Die-cast aluminum head and body for maximum heat dissipation, with integral driver.

**Track Head Adjustability:** 350° horizontal and 90° vertical adjustment.

ELECTRICAL

**Input Voltage:** 120VAC 50/60Hz

**Lumens / Wattage:** 2200lm / 35W per head

**Color Temperature:** 4000K

**Color Rendering Index:** 80+ CRI

**Beam Spread:** 18° Spot or 38° Narrow Flood

**Dimming:** Triac or ELV

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

**Applications:** Excellent choice for high ceiling applications in residential, commercial, retail stores, banquet halls, art and jewelry applications

LISTINGS AND WARRANTY

- cULus Listed for dry locations
- [5-Year Limited Warranty](#)



PRODUCT IMAGES



4' Track Pack with (3) 2200lm Aiden LED Track Heads

Description
NTLE-84240SB = 18° Spot / Black Finish
NTLE-84240FB = 38° Flood / Black Finish

Example: NTLE-84230FB = 4' Track Pack with (3) Aiden LED Track Heads, 3000K / 80 CRI, 38° Flood, Black finish

PHOTOMETRICS

Aiden LED Track Head

Type


Project

Catalog No.

Notes

Test Information

Test Number: 284648  
Part Number: NTE-842L30S35  
Beam Spread: Spot  
Lumens: 2264lm  
Wattage: 35.5W  
Efficacy: 64lpw  
CCT / CRI: 3000K / 80 CRI  
Spacing Criteria (0°-180): 0.32  
Spacing Criteria (90°-270): 0.32



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
6'	360fc	1'-11"
9'	160fc	2'-11"
12'	89.9fc	3'-10"
15'	57.5fc	4'-10"
18'	40fc	5'-8"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	2171	95.9
0-40	2243	99.1
0-60	2262	99.9
0-90	2264	100
90-180	0	0
0-180	2264	100

Candela Table

Vertical Angles	Candela
0	12944
5	10726
15	3043
25	973
35	81
45	19

Test Information

Test Number: 284650  
Part Number: NTE-842L30F35  
Beam Spread: Flood  
Lumens: 2185lm  
Wattage: 34.6W  
Efficacy: 63lpw  
CCT / CRI: 3000K / 80 CRI  
Spacing Criteria (0°-180): 0.64  
Spacing Criteria (90°-270): 0.64



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
6'	149fc	4'-1"
9'	66.1fc	6'-2"
12'	37.2fc	8'-2"
15'	23.8fc	10'-4"
18'	16.5fc	12'-5"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	2068	94.7
0-40	2156	98.7
0-60	2183	99.9
0-90	2185	100
90-180	0	0
0-180	2185	100

Candela Table

Vertical Angles	Candela
0	5357
5	5171
15	3692
25	1298
35	94
45	25