

NTLE-870

4' Track Pack with (3) MAC LED Track Heads

Source: 10W LED per head
700lm per head

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

Track pack comes complete and ready to install with mounting hardware and track heads. Components includes: (1) 4' single circuit track, (2) end caps, (1) floating canopy feed and (3) 700lm MAC LED track heads. The utilitarian style fits almost any design criteria.

FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- Black, silver or White finish
- 700lm / 10W LED output per head
- Field adjustable beam spreads (40° installed and 20° included)
- 2700K, 3000K, 3500K or 4000K
- 80 or 90 CRI
- Dimmable
- Easily to longer lengths or additional track heads
- Perfect for multi family homes or apartments
- 5-Year Limited Warranty

CONSTRUCTION

Housing: Die-cast aluminum construction dissipates heat for longer life.

Adjustability: 350° horizontal and 90° vertical adjustment

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage Per Head: 700lm / 10W

Color Temperature: 2700K, 3000K, 3500K or 4000K

CRI: 80 or 90

Beam Spread: 40° flood installed and 20° spot included

Lifetime: 44,000 hours @ L70

Dimming: ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

One / Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

LABELS AND LISTINGS

- cULus Listed for dry locations
- ENERGY STAR certified
- [5-Year Limited Warranty](#)



PRODUCT IMAGE



4' Track Pack with (3) MAC LED Track Heads

Series	Color Temperature / CRI	Finish
NTLE-870 = 4' Track Pack with (3) MAC LED Track Heads	27 = 2700K / 80 CRI	B = Black
	30 = 3000K / 80 CRI	S = Silver
	40 = 4000K / 80 CRI	W = White
	927 = 2700K / 90 CRI	
	930 = 3000K / 90 CRI	
	935 = 3500K / 90 CRI	
	940 = 4000K / 90 CRI	

Example: **NTLE-87027B** = 4' Track Pack with (3) MAC LED Track Heads, 2700K / 80 CRI, Black Finish

PHOTOMETRICS

MAC LED Track Head

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTR11001
Part Number: NTE-870L272010W
Beam Spread: Spot
Lumens: 713lm
Wattage: 10.7W
Efficacy: 67lpw
CCT / CRI: 2700K / 80 CRI
Spacing Criteria (0°-180°): 0.38
Spacing Criteria (90°-270°): 0.36



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	177fc	1'-6"
6'	78.6fc	2'-4"
8'	44.2fc	3'
10'	28.3fc	3'-10"
12'	19.7fc	4'-6"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	579	81.2
0-40	636	89.2
0-60	686	96.3
0-90	708	99.4
90-180	4	0.6
0-180	713	100

Candela Table

Vertical Angles	Candela
0	2831
5	2568
15	860
25	274
35	88
45	42

Test Information

Test Number: NTR11104
Part Number: NTE-870L274010W
Beam Spread: Flood
Lumens: 691lm
Wattage: 11.2W
Efficacy: 62lpw
CCT / CRI: 2700K / 80 CRI
Spacing Criteria (0°-180°): 0.6
Spacing Criteria (90°-270°): 0.6



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	82.9fc	2'-8"
6'	36.8fc	4'
8'	20.7fc	5'-4"
10'	13.3fc	6'-8"
12'	9.2fc	8'

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	514	74.5
0-40	602	87.2
0-60	661	95.7
0-90	686	99.3
90-180	5	0.7
0-180	691	100

Candela Table

Vertical Angles	Candela
0	1326
5	1264
15	834
25	377
35	139
45	48

Lumen Output Multipliers

Color Temperature: 2700K (1.00), 3000K (0.99), 4000K (1.02)