

# NS-44A / NS-46A

## 4" Adjustable Specular Reflector with Ring

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Adjustable reflector can be adjusted up to 15°.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount lamp into gimbal ring.

### COMPATIBLE HOUSINGS

Compatible with line voltage housings. See individual specification sheets for more information.

### LAMP

#### Line Voltage:

15W R20/PAR20 max. (NS-401AT/IC)

35W R20/PAR20 max. (NFBIC-4INCATA)

50W R20/PAR20 max. (NS-401QAT; NSIC-401QAT; NSR-404QAT; NSRIC-404QAT)

See individual housing specification sheets for more information.

### LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing.




### PRODUCT IMAGES & DIMENSIONS



NS-44A



NS-46A



## 4" Adjustable Specular Reflector with Ring

Catalog No. \_\_\_\_\_

**NS-44A** = 4" Specular Clear Adjustable Reflector with White Metal Ring

**NS-44HZ** = 4" Haze Adjustable Reflector with White Metal Ring

**NS-46A** = 4" Specular White Adjustable Reflector with White Metal Ring

## Compatible Housings

Catalog No. \_\_\_\_\_

**NFBIC-4INCATA** = 2-Hour Fire Rated New Construction / 35W max.

**NS-401QAT** = Non-IC Air-Tight New Construction / 50W max

**NS-401QAT/IC** = IC Air-Tight New Construction / 15W max

**NSIC-401QAT** = IC Air-Tight New Construction / 50W max

**NSR-404QAT** = Non-IC Air-Tight Remodel / 50W max

**NSRIC-404QAT** = IC Air-Tight Remodel / 50W max

Example: **NS-46A** = 4" Specular White Adjustable Reflector with White Metal Ring