

NHIOICD-215 / NHIOICD-220 / NHIOICD-225 NHIOICDCP-215 / NHIOICDCP-220 / NHIOICDCP-225

2" Iolite IC Air-Tight High Lumen New Construction Housing

Source: 20W to 28W LED
1500lm to 2500lm

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

New construction housing for use in insulated ceilings can be in direct contact with insulation**. Air-tight construction provides energy savings by reducing the flow of air through the ceiling. Patented design allows for easy, tool-less removal of the driver.

FEATURES

- IC rated for direct contact with insulation**
- Quick connect provided for electrical connection to the LED reflector
- ASTM E283 for Air-Tight
- Patented driver assembly

SPECIFICATION

Housing: 0.040" Aluminum housing with patented driver assembly, allows for driver to slide out without tools. Housing can be installed in 1/2" ceiling thickness, an extension collar is available for ceiling thickness up to 2", must specify NIO-2EXTC2. Housing allows for access through top plate, for driver maintenance/installation above ceiling.

Air Flow Restriction: Meets requirements of Air-Tight (AT) <2CFM (cubic feet per minute) in accordance with ASTM-283 Air-Tight requirements.

Clearance:** "IC" Insulated ceiling housings are direct contact rated. Not to be used in direct contact with spray foam insulation.

Bar Hangers: Two 13-3/4" to 24-1/2" adjustable bar hangers with captive nails are included on housing. Bar hanger brackets are parallel to junction box, but can be repositioned 90° perpendicular to junction box if desired. "L"-shaped bar hanger foot to align to bottom of construction joist. A T-bar notch allows for easy installation in a suspended ceiling.

Junction Box: Pre-wired 25 cubic inch 0.064" thick galvanized steel, with seven 1/2" knockouts, four Romex® pryouts, and snap on covers. All leads are #18AWG wire, the ground wire is connected to the bottom, and quick connectors are supplied on all leads. Through branch circuit wiring, (4-in, 4-out). Access above ceiling required.

ELECTRICAL

Voltage: 120/277V

Power Factor: >0.90

Operating Temp.:

NHIOICD-215: 0°-40°C (LE4) or 0°-25°C (LUPE0)

NHIOICD-220: 0°-30°C

NHIOICD-225: 0°-25°C

Wattage: 20W, 24W to 28W (must specify)

Dimming: Triac, ELV, 0-10V or EcoSystem (must specify)

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE REFLECTORS

CATALOG NO.	DESCRIPTION
NIOB-2RC	2" Round Cone Regress
NIOB-2SC	2" Square Cone Regress
NIOB-2RG	2" Round Adj. Surface Gimbal
NIOB-2RNDC	2" Round Deep Reflector
NIOB-2SNDC	2" Square Deep Reflector
NIOB-2RPHA	2" Round Adjustable Pinhole
NIOB-2RPH	2" Round Pinhole
NIOB-2SNDSQ	2" Square Reflector / Square Aperture
NIOB-2RSL	2" Round Adj. Slot Aperture
NIOB-2RNB	2" Round Bullnose
NIOB-2SNB	2" Square Bullnose



Emergency: Housing can be specified with connections for emergency battery installation. Requires top access. Must specify housing with remote test switch separately, NEPK-07LEDUNV. *Note: Emergency is not compatible with chicago plenum housings.*

LABELS AND LISTINGS

- cULus Listed for Damp Location (Wet Location when used with compatible reflector)
- [5-Year Limited Warranty](#)
- RoHS Compliant
- FCC compliant
- Patent #D824567S
- Meets or exceeds ASTM-283 Air-Tight requirements



PRODUCT IMAGES AND DIMENSIONS



2" Iolite ICAT High Lumen New Construction Housing - Compatible with NIOB-2 & NIO-2 reflectors

Housing Type / Lumens / Wattage	Driver / Dimming	Optional Emergency
NHIOICD-215 = IC Air-Tight, 1500lm / 20W	LE4 = 120/277V input; Triac / ELV / 0-10V dimming LUPE0 = 120/277V input; Lutron Hi-lume Premier 0.1% EcoSystem with Soft-On, Fade-to-Black LUPE01 = 120/277V input; Lutron Hi-lume 1% EcoSystem with Soft-On, Fade-to-Black	/PEM = Pre-Wired for Remote Emergency
NHIOICD-220 = IC Air-Tight, 2000lm / 24W NHIOICD-225 = IC Air-Tight, 2500lm / 28W	LE4 = 120/277V input; Triac / ELV / 0-10V dimming	/PEM = Pre-Wired for Remote Emergency
NHIOICDCP-215 = Chicago Plenum, 1500lm / 20W	LE4 = 120/277V input; Triac / ELV / 0-10V dimming LUPE0 = 120/277V input; Lutron Hi-lume Premier 0.1% EcoSystem with Soft-On, Fade-to-Black LUPE01 = 120/277V input; Lutron Hi-lume 1% EcoSystem with Soft-On, Fade-to-Black	
NHIOICDCP-220 = Chicago Plenum, 2000lm / 24W NHIOICDCP-225 = Chicago Plenum, 2500lm / 28W	LE4 = 120/277V input; Triac / ELV / 0-10V dimming	

Optional Accessories

Description
NEPK-07LEDUNV = Remote Emergency Battery w/Test Switch
NIO-2EXTC2 = Ceiling Extension Collar up to 2"

Example: **NHIOICD-220LE4** = 2" Iolite ICAT High Lumen New Construction Housing, 2000lm / 24W, 120-277V input; Triac / ELV / 0-10V dimming