

iPOINT

1" and 2" Adjustable LED Monopoints 750 to 1200 lumens

The iPOINT LED monopoint is the newest addition to the Iolite family. iPOINT luminaires require an Iolite housing, allowing the fixture to maintain a minimal canopy and sleek appearance. iPOINT fixtures produce from 750 to 1200 lumens at 90+ CRI with a choice of three kelvin temperatures from 2700K, 3000K or 4000K. Similar to Iolite reflectors, each iPOINT includes spot, narrow flood and flood optics which can be easily changed in the field. iPOINT is available in Cylinder or Cone styles in black or matte powder white. iPOINT luminaires can be dimmed with Triac, ELV, 0-10V or Lutron Hi-lume EcoSystem.

FEATURES

- Architectural die-cast aluminum construction
- Cree® Chip On Board (COB) LED technology
- Includes Spot, Narrow Flood and Flood field-changeable optics
- Cone and Cylinder styles in two sizes:
 - 1" Cone - 900lm / 9W or 10W (specified by housing)
 - 1" Cylinder - 750lm / 9W or 10W (specified by housing)
 - 2" Cone - 1200lm / 14W
 - 2" Cylinder - 1000lm / 14W
- 2700K, 3000K or 4000K at 90+ CRI
- Requires an Iolite Recessed Housing
- Dimmable (specified by housing)
- Black or Matte Powder White finish
- cULus Listed for Damp Location
- ENERGY STAR® certified
- 5-Year Limited Warranty



iPOINT LED MONOPOINTS

FIXTURE TYPE & LUMENS	CCT	FINISH
NIOP-1RCY 1" Cylinder / 750lm	27X 2700K	BB Black
NIOP-1RTC 1" Cone / 900lm	30X 3000K	MPW Matte Powder White
NIOP-2RCY 2" Cylinder / 1000lm	40X 4000K	(Includes Black insert)
NIOP-2RTC 2" Cone / 1200lm		

Example: **NIOP-2RTC27XMPW** - 2" iPOINT Cone - 1200lm, 2700K / 90 CRI, Matte Powder White



NIOP-1RTC

L: 3-1/8"
Dia: 2-3/4"

shown with and without
black reflector insert

NIOP-2RTC

L: 3-5/8"
Dia: 3-1/4"



NIOP-1RCY

L: 4"
Dia: 1-5/8"

NIOP-2RCY

L: 4-3/4"
Dia: 2-3/8"

shown with and without
black reflector insert

