

# 6" LED CYLINDERS

Wall, Stem, Surface or Cable Mounted  
750 to 3500 Lumens

6" Cylinders can be fitted with our Cobalt and Sapphire II light engines to achieve anywhere from 750lm to 3500lm in 2700K, 3000K, 3500K, and 4000K. Cylinders can be wall mounted, cable mounted, surface mounted, and stem mounted to meet any installation requirement.

## FEATURES

- Over 80% energy savings when compared to incandescent
- Stem, Surface, Cable or Wall Mounted
- Dedicated CCT (27K, 30K, 35K, 40K) @ 90+ CRI
- 120-277V input with Triac / ELV or 0-10V dimming options
- Reflector, Baffle or Decorative Glass Trims
- Available in variety of architectural finishes
- 5-Year limited warranty
- ENERGY STAR® certified
- Assembled in USA
- cULus Listed for Damp Locations (Wall Mount is Wet Rated)



**NYLD2-6S**  
Surface Mounted  
Cobalt



**NYLS2-6W**  
Wall Mounted  
Sapphire II



**Sloped Ceiling**  
canopy included  
with stem mount

**NYLD2-6P**  
Stem Mounted  
Cobalt



**NYLS2-6C**  
Cable Mounted  
Sapphire II

6" CYLINDERS								
	MOUNTING	LUMENS / WATTAGE	TRIM TYPE	CCT	BEAM SPREAD	TRIM / FLANGE FINISH	CYLINDER FINISH	DIMMING
<b>SAPPHIRE II</b>	<b>NYLS2-6P</b> = Stem	<b>09</b> = 900lm / 16W	<b>1</b> = Reflector	<b>27</b> = 2700K	<b>S</b> = Spot	<b>BB</b> = Black/Black	<b>DW</b> = Diffused/White	<b>B</b> = Black
	<b>NYLS2-6C</b> = Cable	<b>15</b> = 1500lm / 18W	<b>2</b> = Reflector for Deco Glass*	<b>30</b> = 3000K	<b>M</b> = Narrow	<b>BW</b> = Black/White	<b>HW</b> = Haze/White	<b>W</b> = White
	<b>NYLS2-6S</b> = Surface	<b>25</b> = 2500lm / 27W		<b>35</b> = 3500K	<b>F</b> = Flood	<b>CC</b> = Clear/Clear	<b>HZ</b> = Haze/Haze	
	<b>NYLS2-6W</b> = Wall Wash	<b>35</b> = 3500lm / 46W		<b>40</b> = 4000K		<b>DD</b> = Diffused/Diffused	<b>WW</b> = White/White	<b>3</b> = 120V Triac/ELV <b>6</b> = 120-277V 0-10V
<b>COBALT</b>	<b>NYLD2-6P</b> = Stem	<b>075</b> = 750lm / 10W	<b>1</b> = Reflector	<b>27</b> = 2700K		<b>BB</b> = Black/Black	<b>HZW</b> = Haze/White	<b>B</b> = Black
	<b>NYLD2-6C</b> = Cable	<b>10</b> = 1000lm / 12W	<b>2</b> = Baffle	<b>30</b> = 3000K		<b>BW</b> = Black/White	<b>MPW</b> = Matte Powder White	<b>W</b> = White
	<b>NYLD2-6S</b> = Surface			<b>35</b> = 3500K		<b>BZ</b> = Bronze/Bronze	<b>NN</b> = Natural Metal	
	<b>NYLD2-6W</b> = Wall Wash			<b>40</b> = 4000K		<b>CO</b> = Copper/Copper	<b>WW</b> = White/White	<b>3</b> = 120V Triac/ELV <b>6</b> = 120/277V 0-10V

Example: **NYLS2-6S35135DDWW6** = 6" Sapphire II Cylinder, Surface Mounted, 3500lm / 46W, 3500K, Diffused Reflector / White Flange, White Cylinder, 120-277V input; 0-10V dimming