

6" LED CYLINDERS

Wall, Stem, Surface or Cable Mounted
750 to 5500 Lumens

6" Cylinders can be fitted with our Cobalt and Sapphire III light engines to achieve anywhere from 750lm to 5500lm in 2700K, 3000K, 3500K, and 4000K. Cylinders can be wall mounted, cable mounted, surface mounted, and stem mounted to meet any installation requirement.

FEATURES

- Over 80% energy savings when compared to incandescent
- Stem, Surface, Cable or Wall Mounted
- Dedicated CCT, Selectable CCT or Comfort Dim (Warm Dim)
- 120-277V input with Triac / ELV or 0-10V dimming options
- Reflector, Baffle or Decorative Glass Trims
- Available in variety of architectural finishes
- 5-Year limited warranty
- cULus Listed for Damp Locations (Wall Mount is Wet Rated)



NYLD2-6S
Surface Mounted
Cobalt



NYLS3-6W
Wall Mounted
Sapphire III



NYLD2-6P
Stem Mounted
Cobalt



Sloped Ceiling
canopy included
with stem mount



NYLS3-6C
Cable Mounted
Sapphire III

6" COBALT CYLINDERS (UP TO 1000 LUMENS) Sapphire III

MOUNTING	LUMENS	TRIM TYPE	CCT	TRIM / FLANGE FINISH	CYLINDER FINISH	DIMMING
NYLD2-6P = Stem NYLD2-6C = Cable NYLD2-6S = Surface NYLD2-6W = Wall Wash	075 = 750lm 10 = 1000lm	1 = Reflector 2 = Baffle	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K TW = Selectable CCT CD = Comfort Dim	BB = Black/Black BW = Black/White BZ = Bronze/Bronze CO = Copper/Copper HZW = Haze/White MPW = Matte Powder White NN = Natural Metal WW = White/White	B = Black W = White	3 = 120V Triac/ELV 6 = 120/277V 0-10V

Example: **NYLD2-6S10135WWW6** = 6" Cobalt Cylinder, Surface Mounted, 1000lm / 12W, 3500K, White Reflector / White Flange, White Cylinder, 120-277V input; 0-10V dimming

6" SAPPHIRE III CYLINDERS (UP TO 5500 LUMENS)

MOUNTING	TRIM TYPE	LUMENS / WATTAGE	CCT	BEAM SPREAD	DIMMING	TRIM / FLANGE FINISH	CYLINDER FINISH	OPTIONAL EM
NYLS3-6P = Stem NYLS3-6C = Cable NYLS3-6S = Surface NYLS3-6W = Wall Wash	1 = Reflector 6 = Wall Wash ¹ 8 = Reflector for Deco Glass* ¹ ¹ Not compatible with L6 * Decorative glass ordered separately	L1 = 900lm / 11W L2 = 1500lm / 16W L3 = 2500lm / 24W L4 = 3500lm / 36W L5 = 4500lm / 44W L6 = 5500lm / 58W	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	S = Spot N = Narrow F = Flood	P01 = 120V Triac/ELV C12 = 120-277V 0-10V	BB = Black/Black BW = Black/MPW CC = Clear/Clear DB = Diffused/Black DD = Diffused/Diffused DW = Diffused/MPW HB = Haze/Black HW = Haze/MPW HZ = Haze/Haze WW = Matte Powder White	B = Black W = White	/PEM = Pre-Wired for remote emergency

Example: **NYLS3-6S1L635SC12DWW** = 6" Sapphire III Cylinder, Surface Mounted, 5500lm / 58W, 3500K, Diffused Reflector / White Flange, White Cylinder, 120-277V input; 0-10V dimming