# NMT-48/24C2D1

24V Dimmable Class II Hardwire Magnetic Driver

Source: 120V Input / 24V Output

48W

Туре		
Project		
Catalog No.		
Notes		

#### PRODUCT DESCRIPTION

24V enclosed dimmable driver to be used with Nora Lighting's 24 Volt systems requiring a Class II driver. Produces 48 watts and can be dimmed with low voltage magnetic dimmer. Includes a regulator to provide constant current and constant voltage.

#### **FFATURES**

- · Fully dimmable with low voltage magnetic dimming
- · Integral regulator for constant current and voltage
- · Manual Reset Overload Protection for each Class II Circuit
- · Indoor/Outdoor Enclosure Type 3R Enclosure
- · Conduit Access Wiring Compartment
- · Made in USA
- · Meets Class II output limits
- · 24 Volt DC Rated output
- · cULus Listed & CSA approved

# **ELECTRICAL**

Input Voltage: 120V

Output Voltage: 24VDC, 2A max.

Wattage: 48W

**Dimming:** Magnetic Low Voltage

Regulator: Constant Current and Constant Voltage

### **COMPATIBLE NORA 12V SYSTEMS**

LED Drivers are compatible with Nora Lighting's 24V systems

SERIES	DESCRIPTION
NMP2-A	24V Josh Adjustable
NMP2-LED	24V Josh Fixed
NUTP5	24V Hy-Brite Tape Light
NUTP8	24V High Output Tape Light
NUTP9	24V Side-Lit Tape Light
NUTP10	24V CCT Color Changing Tape Light
NUTP12	24V Comfort Dim (warm dim) Tape Light
NUTP14	24V COB High Output Tape Light
NUTP15	24V COB Standard Output Tape Light
NUTP51	24V Continuous Hy-Brite Tape Light
NUTP71	24V Continuous Standard Tape Light
NUTP81	24V Continuous High Output Tape Light
NULB	24V Lightbar Silk SBC

# OPTIONAL ACCESSORIES

NALTL-10: 10' Power Line Connector (included)

NALTL-30: 30' Power Line Connector


NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.

#### LABELS AND LISTINGS

- · Three Year Limited Warranty
- · cULus Listed
- · CSA approved



## **PRODUCT IMAGES & DIMENSIONS**



NMT-48/24C2D1 24V Dimmable Class II Hardwire LED Driver MLV dimming



NALTL-10 / NALTL-30 Power Line Connector



**NATL-302W** Power Line Splitter

# 24V Dimmable Class II Hardwire Magnetic Driver

Output Voltage / Wattage

NMT-48/24C2D1 = 24V Ouput / 48W

Optional Accessories

Description

NALTL-10 = 10' Power Line Connector NALTL-30 = 30' Power Line Connector NATL-302W = Power Line Splitter, White

Example: NMT-48/24C2D1 = 24V 48W Dimmable Class II Hardwire Magnetic Driver

