

# PEARL

# 4", 5" & 6" LED Retrofit Delivering over 1000 lumens

Pearl LED Retrofit series is cULus classified for use in existing IC or non-IC housings manufactured by Nora and others. The 4" retrofit luminaires produce up to 1200 lumens with die-cast round and square reflectors and field changeable optics.

# **FEATURES**

- · Up to 1200lm LED output (800lm with Comfort Dim technology)
- 2700K, 3000K, 3500K, 4000K or Comfort Dim
- · 90+ Color Rendering Index
- · COB LED or Comfort Dim Technology
- · Field changeable optics included (Spot, Narrow Flood and Flood - installed)
- · Integral dimmable driver (Triac or ELV)
- · Compatible with shallow housings and most IC and non-IC housings by Nora and others
- · Includes medium base socket adapter for easy retrofitting
- · cULus classified for wet locations (adjustable reflectors are damp location)
- · ENERGY STAR® certified
- · 5-Year Limited Warranty
- · Certified to the high efficacy requirements of California Title 24 JA8-2022



















# **Medium Base Socket Adapter**

included with each luminaire for easy retrofitting in recessed housings

#### **Integral Driver**

Triac / ELV dimming

**Die-Cast Aluminum Heat Sink** with COB LED technology

# **Compatible with Shallow Housings!**

Luminaires designated with the **SH** shallow icon are compatible with shallow plenum housings







**FLOOD** Field Changeable Optics

Each module includes spot, narrow flood and flood optics

# **Optional Accessories**

can be added anytime between reflector and LED module





APERTURE / SHAPE	TRIM TYPE	
NPR-4R 4" Round NPR-4S 4" Square	C G NB NDC PH PHA SL NDSQ	Adjustable Cone SH Adjustable Gimbal SH Non-Adjustable Bullnose ISH Non-Adjustable Reflector w/Round Aperture ISH Non-Adjustable Pinhole ISH Adjustable Pinhole ISH Adjustable Slot Aperture Non-Adjustable Reflector w/Square Aperture ISH
NPR-56R 5"/6" Round	NDC	Non-Adjustable Reflector w/Round Aperture 🚾

CCT 27X 2700K / 1200lm BB

**30X** 3000K / 1200lm **35X** 3500K / 1200lm

40X 4000K / 1200Im CDX Comfort Dim / 800lm FINISH (not all finishes available on all reflectors)

Black / Black Flange **BMPW** Black / Matte Powder White Flange BW Black / White Flange ΒZ Bronze / Bronze Flange

CMPW Specular Clear / Matte Powder White Flange CHMPW Champagne Haze / Matte Powder White Flange HW Haze / White Flange

**HZMPW** Haze / Matte Powder White Flange

MPW Matte Powder White / Matte Powder White Flange NN Natural Metal / Nat. Metal Flange ww White / White Flange

Example: NPR-4RC30XWW - 4" Pearl LED Round Adjustable Cone Retrofit, 3000K / 1200lm, White with White Flange

WWW NORALIGHTING COM ML-PEARLF0623

# 4", 5" & 6" PEARL LED RETROFIT





# NPR-4RC

SH 4" Round Adjustable Cone Regress BB, BW, BZ, CMPW, HW, HZMPW, MPW, NN, WW 10°-35° Adjustable (determined by housing)



## NPR-4SC

SH 4" Square Adjustable Cone Regress BB, BW, BZ, CMPW HW, HZMPW, MPW, NN, WW

10°-35° Adjustable (determined by housing)



#### NPR-4RG

SH 4" Round Adjustable Gimbal BB, BZ, MPW, NN, WW

10°-35° Adjustable (determined by housing)



## NPR-4SG

SH 4" Square Adjustable Gimbal BB, BZ, MPW, NN, WW 10°-35° Adjustable (determined by housing)



# NPR-4RNB

4" Round Bullnose BB, BZ, MPW, NN, WW Non-Adjustable



# NPR-4SNB

4" Square Bullnose BB, BZ, MPW, NN, WW Non-Adjustable



# NPR-4RNDC

4" Round Reflector w/ Round Aperture BB, BW, BZ, CMPW, CHMPW, HW, HZMPW, MPW, NN, WW Non-Adjustable



# NPR-4SNDC

4" Square Reflector w/ Round Aperture BB, BW, BZ, CMPW, CHMPW, HW, HZMPW, MPW, NN, WW Non-Adjustable



# NPR-4RPH 4" Fixed Pinhole **NPR-4RPHA**

4" Adjustable Pinhole - 30° BB, BMPW, HZMPW, MPW



# NPR-4RSL

4" Round Adjustable Slot Aperture BB, BMPW, HZMPW, MPW 30° Adjustable



#### NPR-4SNDSQ

4" Square Reflector w/ Square Aperture BB, BW, BZ, CHMPW, HN, HW, HZMPW, MPW, WW Non-Adjustable



# NPR-56RNDC

5"/6" Round Reflector BB, BW, CHMPW, MPW, WW Non-Adjustable

# TRIM FINISHES























(SH designates trims compatible with shallow housings)

**ACCESSORIES** Optional accessories easily install between module and die-cast trim at any point in the design process.



## **Frosted Optics** 60° or 73°

Replaces optics included with each LED module



**Premium TIR Optic** 22° or 26°

Not compatible with Comfort Dim Module



## **Opaque Collar Snoot** 5/8", 3/4" or 1"

Black, Matte Powder White or White



#### **Translucent Deco Collar**

5/8", 3/4" or 1" Blue, Frost, Amber or Red



# **Hex Cell Louver**

Reduces aperture brightness and light output by about 20%