

# NELOCAC-16R

16" ELO LED Surface Mount Luminaire

Source: 20W LED  
2100lm

## PRODUCT DESCRIPTION

16" ELO LED Surface Mount is a thin 1" luminaire that mounts easily over a standard or fire rated junction boxes.

## FEATURES

- Delivering up to 2100 lumens
- 2700K, 3000K or 4000K @ 90+ CRI
- Easily surface mounts over junction box
- Can be suspended from ceiling with pendant or stem kit accessory
- Dimmable with Triac or ELV dimmer
- 5-year limited warranty

## MOUNTING

**Surface Mount:** Steel bracket mounts on junction box and luminaire twist and locks onto steel bracket.

Compatible Junction Boxes:

- 3" and 4" Octagonal
- 4" Square
- 4" Pancake
- 4" Plastic Round

**Cable Mount:** Pendant kit (ordered separately) can be used to suspend luminaire up to 4'.

**Stem Mount:** Stem kit (ordered separately) can be used to suspend luminaire from swivel canopy from 1' to 7' (must specify). Swivel canopy is compatible with sloped ceilings with a ceiling pitch from 1/12 to 10/12.

## ELECTRICAL

**Input Voltage:** 120-277V

**Delivered Lumens / Wattage:** 2100lm / 20W

**Color Temperature:** 2700K, 3000K or 4000K

**Color Rendering Index:** 90+ CRI

**Lifetime:** 54,000 Hours @ L70

**Operating Temperature:** 0°C to 40°C ambient temperature

**Dimming:** Triac or ELV @ 120V only

[Click Here](#) or check complete dimmer list at [www.NoraLighting.com](http://www.NoraLighting.com) in the "Compatibility" page under "Resources" tab

## OPTIONAL ACCESSORIES

[NELOCAC-16PK](#) = 4' Pendant Kit

[NELOCAC-16ST](#) = Stem Mount Kit, must specify length

## LABELS AND LISTINGS

- cETLus Listed for Damp Location
- ENERGY STAR certified
- FCC Listed
- 5-Year Limited Warranty
- Certified to the high efficacy requirements of California Title 24 JA8-2022
- Suitable for use in closets when installed in accordance to NEC Section 410.16 (A)(1) and 410.16 (C)(1).



Type

Project


Catalog No.

Notes

## Performance Data

Part Number	Lumens	CCT
<b>NELOCAC-16R927W</b>	1738lm	2700K
<b>NELOCAC-16R930W</b>	1922lm	3000K
<b>NELOCAC-16R940W</b>	2097lm	4000K

## PRODUCT IMAGES & DIMENSIONS



**NELOCAC-16R**  
16" ELO



**NELOCAC-16PK**  
Pendant Kit



**NELOCAC-16ST**  
Stem Kit

## 16" ELO LED Surface Mount Luminaire

CCT / CRI / Finish

**NELOCAC-16R927W** = 2700K / 90+ CRI / White Finish

**NELOCAC-16R930B** = 3000K / 90+ CRI / Black Finish

**NELOCAC-16R930W** = 3000K / 90+ CRI / White Finish

**NELOCAC-16R940W** = 4000K / 90+ CRI / White Finish

## Optional Mounting Accessory

Description	Finish	Length
<b>NELOCAC-16PK</b> = Pendant Kit	<b>B</b> = Black	<b>(blank)</b> = 4'
	<b>W</b> = White	
<b>NELOCAC-16ST</b> = Stem Kit	<b>B</b> = Black	<b>/12</b> = 1'
	<b>W</b> = White	<b>/24</b> = 2'
		<b>/36</b> = 3'
		<b>/48</b> = 4'
		<b>/60</b> = 5'
		<b>/72</b> = 6'
		<b>/84</b> = 7'

Example: **NELOCAC-16R930W** = 16" ELO LED Surface Mount Luminaire, 3000K / 90+ CRI, White finish