

NUTP13-W150

150' 120VAC Continuous IP65 Rated LED Tape Light  
Source: 3.6W/ft. LED  
330lm/ft.

PRODUCT DESCRIPTION

120VAC IP65 Rated LED Tape is the perfect solution for indoor or outdoor applications without the need for LED drivers. Producing up to 330 lumens per foot, tape light can be ordered with cord and plug, or hardwired for dimming. The low profile tape is the ideal for coves, architectural details, under and in cabinets, toe kicks, and back lighting.

FEATURES

- IP65 rated for wet locations
- 120VAC system - integrated LED driver
- Hardwired or Cord & Plug
- 330 lumens / 3.6W per foot
- Available in dedicated color temperature (2700K, 3000K or 4000K)
- Mounting clips included and aluminum channels available

SPECIFICATION

**Construction:** 150' spool (actual length 150.53') is cuttable every 4" (cutting the tape voides ETL and warranty). Power cord, end cap and mounting clips are included. IP65 rating is resistant to dust and protected against water projected by a nozzle.

**Note:** Tape light is non-submersible and cutting tape in the field will void ETL and warranty

**Power Feed:** Continuous LED Tape comes standard with a 8' cord and plug or 8' hardwire cable (2-wire). Power feed can support lengths up to 150'.

**Mounting:** Optional aluminum channels and mounting clips are available. Recommended mounting clip distance is 1' apart.

**NATL-CIP25A:** 4' Deep Recessed Channel, Aluminum (NUTP13-ADHTAPE included)

**NATL-CIP26A:** 4' Deep Channel, Aluminum (NUTP13-ADHTAPE included)

**NATL-CIP26W:** 4' Deep Channel, White (NUTP13-ADHTAPE included)

**NUTP13-ADHTAPE:** 3M™ Adhesive Tape (ordered by foot, 108' max. length)

**NATL-IP6512:** Mounting Clips (Pack of 2), Clear [Two included per foot]

**NATL-IP65/SP:** External Surge Protector (for Hardwire only)

ELECTRICAL

**Input Voltage:** 120VAC

**Lumens / Wattage:** 330lm / 3.6W per foot

**Color Temperature:** 2700K, 3000K or 4000K

**Color Rendering Index:** 90+ CRI

**Beam Spread:** 110° Wide Flood

**Operating Temperature:** -20°C to 45°C

**Dimming:** Triac

**Run Length:** 150' maximum

**Ground Fault Circuit Interrupter:** Luminaire must be installed only on GFCI protected circuits. Do not install near water or where other liquids may accumulate. Product must be installed under covered ceiling.

**Surge Protector:** Tape light is recommended to be used with surge protector accessory when installed outdoors or longer run lengths, ordered separately (NATL-IP65/SP). Compatible with hardwired tape light sections only.


LABELS AND LISTINGS

- ETLus Listed for Wet Locations (Void if field cut)
- IP65 rated (Void if field cut)
- RoHS compliant
- 3-Year Limited Warranty for Outdoor Applications
- 5-Year Limited Warranty for Indoor Applications



Type
Project
Catalog No.
Notes

PRODUCT IMAGES & DIMENSIONS



150' 120VAC Continuous IP65 Rated LED Tape Light

Description	Power Cord
NUTP13-W150-12-927 = 150' Roll / 2700K	/HW = 8' Hardwired
NUTP13-W150-12-930 = 150' Roll / 3000K	/HWSP = 8' Hardwired with Surge Protector
NUTP13-W150-12-940 = 150' Roll / 4000K	/CP = 8' Cord and Plug
	/CPSP = 8' Cord & Plug with Surge Protector

Optional Mounting Accessories

Description
NATL-CIP25A = 4' Deep Recessed Channel, Aluminum (NUTP13-ADHTAPE incl.)
NATL-CIP26A = 4' Deep Channel, Aluminum (NUTP13-ADHTAPE included)
NATL-CIP26W = 4' Deep Channel, White (NUTP13-ADHTAPE included)
NUTP13-ADHTAPE = 3M™ Adhesive Tape (ordered by foot, 108' max.)
NATL-IP6512 = Mounting Clips (Pack of Two), Clear [2 included per ft.]
NATL-IP65/SP = External Surge Protector (for Hardwire only)

Example: NUTP13-W150-12-930/CP = 150' 120VAC Continuous IP65 Rated LED Tape Light, 540W, 3000K, 8' Cord and Plug

## NUTP13 Series

120VAC Continuous IP65 Rated LED Tape Light Accessories

**Note:** All accessories are factory installed, nonreturnable and noncancelable

**Note:** Tape light is non-submersible and cutting tape in the field will void ETL and warranty

Type

Project

Catalog No.


Notes



Hardwire Power Cord (/HW)

8' Hardwire cord used to power 120V tape light and connect to compatible dimmer.

**Factory installed only. Not sold separately.**



Hardwire w/ Surge Protector (/HWSP)

8' Hardwire cord with integral surge protector. Used to power 120V tape light, connect to compatible dimmer and protect from potential surges in voltage.


**Factory installed only. Not sold separately.**



Cord & Plug (/CP)

8' Cord and plug used to power 120V tape light.


**Factory installed only. Not sold separately.**



Cord & Plug w/ Surge Protector (/CPSP)

8' Cord and plug with integral surge protector. Used to power 120V tape light and protect from potential surges in voltage.

**Factory installed only. Not sold separately.**



Extension Cables

**NATL-IP65/EW-03**


3" Cable

**NATL-IP65/EW-06**

6" Cable

Cable used to connect two sections of NUTP13 tape light.

**Factory installed only. Not sold separately.**




90° Left Connector

**NATL-IP65/C90-L**

90° Left connector used to connect two sections of NUTP13 tape light.

**Factory installed only. Not sold separately.**



90° Right Connector

**NATL-IP65/C90-R**

90° Right connector used to connect two sections of NUTP13 tape light.

**Factory installed only. Not sold separately.**



4' Deep Recessed Channel


**NATL-CIP25A**

Aluminum Finish

Used to mount NUTP13 tape light recessed in a surface. 4' length and field cuttable. Adhesive tape and diffused lens are included. Wing can be used to recess channel. **Sold separately.**

**Note:** Channel is not compatible with the following:

- NATL-IP65/C90-R
- NATL-IP65/C90-L



4' Deep Channel

**NATL-CIP26A**

Aluminum Finish

**NATL-CIP26W**

White Finish

Used to mount NUTP13 tape light to flat surface. 4' length and field cuttable. Adhesive tape and diffused lens are included.

**Sold separately.** Note: Channel is not compatible with the following:

- NATL-IP65/C90-R
- NATL-IP65/C90-L




Clear Mounting Clips

**NATL-IP65I2**

Pack of Two

Used to mount NUTP13 tape light to flat surface. Two clips are included per foot with NUTP13 tape light. **Sold separately.**



External Surge Protector

**NATL-IP65/SP**

Hardwire Only (/HW)

Can only be used with Hardwire power cord only (/HW). Must be installed in compliance with electrical codes. **Sold separately.**