NUDTW-88/23345	Туре
LEDUR 120V Edge-Lit Under Cabinet - Selectable Lumens & CCT Source: 7W to 16W	Project
275lm or 475lm per foot	Catalog No.
	Notes
PRODUCT DESCRIPTION LEDUR LED Under cabinet luminaires include two switches to change the color temperature and lumen output. Five color temperature options and two lumen outputs creates ten different fixtures in one! Color temperature options range from 2700K, 3000K, 3500K, 4000K or 5000K @ 90 CRI. Luminaires produces an 275 lumens or 475 lumens average per foot. LEDU uniform reflectance is excellent when used under cabinet over granite, polished stone or any reflective surface, additional is excellent in retail display lighting where diode image might distract from display merchandise.	
 FEATURES Ten fixtures in one! (5 CCT options and 2 lumen outputs) Five color temperatures in each fixture (2700K / 3000K / 3500K / 4000K / 5000K) Two lumen outputs in each fixture (275lm or 475lm per foot) Edge lit design eliminates LED diode image Available in five different lengths Dark Bronze or White Finish Built-in on/off rocker switch Linkable up to 400 Watts fixtures 3 wire grounded electrical port on both ends for power or linking Quick connect stab-in connectors included Captive Screws for easy mounting Integral dimmable driver 	Selectable CCT
ELECTRICAL Input Voltage: 120V Lumens: 275Im or 475Im per foot (field selectable) Wattage: 11" = 7W; 18" = 9W; 22" = 11W; 32" = 16W; 42" = 16W Color Temperature: Selectable CCT: 2700K / 3000K / 3500K / 4000K / 5000K (<u>Note</u> : Preset to 3000K) Color Rendering Index: 90+ CRI Operating Temp:: 0°C to 45°C ambient temperature Maximum Run Length: 400W Dimming: Triac or ELV Click Here or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab.	Five position sliding switch 27K / 30K / 35K / 40K / 50k 3 position lumen selection rocker switch Captive Screws for easy mounting located at each end under removable cap
CONSTRUCTION Housing: Rear wireway access cover with stab-in electrical connectors facilitate wiring without opening the fixture. Additional knock-outs for top and back wiring.	
nstallation: Mounting hardware is included with each unit. Captive screws allow for quick installation, simply wire using ear door and quick connects, and hold in place and drive captive screws into material. Captives screws are covered with a ncluded cap for a beautiful finished look.	In Length
ncluded with every fixture: Mounting Hardware and ½" die-cast metallic cable clamp, end to end connector, lumen outpu witch and color temperature switch.	It NUDTW-8811 11-1/4" NUDTW-8818 18-1/4" NUDTW-8822 22-1/4"
ABELS AND LISTINGS cULus Listed for Damp Location <u>5-Year Limited Warranty</u> Certified to the high efficacy requirements of California Title 24 JA8-2022	NUDTW-8822 22-2/4 NUDTW-8832 32-3/4" NUDTW-8842 42"
	NUDIW-8842 42"

LEDUR 120V Edge-Lit Under Cabinet - Selectable Lumens and CCT



Example: NUDTW-8822/23345WH = 22" LEDUR 120V Edge-Lit Under Cabinet, Selectable Lumens and CCT, White Finish



NUDTW-88/23345

LEDUR 120V Edge-Lit Under Cabinet - Selectable CCT & Output Source: 7W to 16W

275lm or 475lm per foot

Type Project Catalog No.

Notes



Junction Box

NUA-802B Black NUA-802W White Used to power NUDTW-88 series using Jumper Cables or NUA-804 Hardwire Connector. Finish: Black or White



End to End Connector

NUA-803 Used to join two NUDTW-88 fixtures seamlessly together. 3-wire grounded connector. Finish: White



72" 3-Wire Grounded Hardwire Connector

 NUA-804B
 Black

 NUA-804W
 White

 Used to hardwire NUDTW-88 fixtures to
 NUA-802 or junction box (by others).

 Finish: Black or White
 Finish: Black or White



72" Cord & Plug

NUA-805BBlackNUA-805WWhiteConvert NUDTW-88 series fixtures fromhardwire to direct plug-in units.Finish: Black or White



Jumper Cable

NUA-806B	6" Black
NUA-806W	6" White
NUA-812B	12" Black
NUA-812W	12" White
NUA-824B	24" Black
NUA-824W	24" White
NUA-872B	72" Black
NUA-872W	72" White
Used to join NUDTW-88 fixture	es
together or to NUA-802.	
Finish: Black or White	