

M-CURVE SERIES

Adjustable Can-less Downlights 80° Tilt & 360° Rotation (No Housing Required!)

M-Curve adjustable can-less LED downlights features single axis rotation with **80° tilt and 360° rotation**. 4" and 6" Can-less downlights are easy to install in new construction or remodel applications. Junction box includes a **five CCT switch** to change the color temperature from 2700K to 5000K.

FEATURES

- Two sizes and outputs (900lm or 1300lm)
- 80° Tilt & 360° Rotation
- No housing required and includes pre-wired junction box
- Quick disconnect allows for easy installation
- Junction box includes selectable color temperature switch
- IC Air-Tight rated
- Available in two sizes (4" & 6")
- Five color temperatures in each fixture
(2700K / 3000K / 3500K / 4000K / 5000K)
- 120V input with Triac or ELV dimming
- cETLus Listed for Wet locations
- ENERGY STAR certified
- Certified to the high efficacy requirements of California Title 24 JA8-2022



M-CURVE ADJUSTABLE CAN-LESS DOWNLIGHTS

DESCRIPTION

NMC-4RTWMPW	4" M-Curve, 900lm / 9W, Selectable CCT
NMC-6RTWMPW	6" M-Curve, 1300lm / 13.5W, Selectable CCT

OPTIONAL ACCESSORY

DESCRIPTION

NF-R375	New Construction Frame-In for NMC-4RTWMPW
----------------	---

