

Multiple Lighting System Comparison Chart

NMRG2



NMRG3



Housing Type (Part Numbers)	One Head / Non-IC (NMRG2-11) One Head / Non-IC (NMRG2-12) One Head / Non-IC (NMRG2-13)	One Head / IC (NMRGIC3-1) One Head / Non-IC (NMRG3-1) Two Head / IC (NMRGIC3-2) Two Head / Non-IC (NMRG3-2) Three Head / IC (NMRGIC3-3) Three Head / Non-IC (NMRG3-3)
Lumens / Wattage (Part Numbers)	900lm / 16W (L09) 1500lm / 18W (L15) 2500lm / 27W (L25)	900lm / 11W (L1) 1500lm / 16W (L2) 2500lm / 26W (L3) 3000lm / 32W (L4) 3500lm / 38W (L5)
Input Voltage / Dimming Type (Part Numbers)	D3 (120V input; Triac/ELV/0-10V Dimming) D6 (120-277V input; 0-10V Dimming)	P01 (120V input; Triac/ELV Dimming) C12 (120-277V input; 0-10V Dimming)

NMRT2



NMRT3



Trim Type (Part Numbers)	One Head / Flat (NMRT2-1F1) One Head / Regressed (NMRT2-11) Two Head / Flat (NMRT2-1F2) Two Head / Regressed (NMRT2-12) Three Head / Flat (NMRT2-1F3) Three Head / Regressed (NMRT2-13)	One Head / Flat (NMRT3-1F) One Head / Regressed (NMRT3-1R) Two Head / Flat (NMRT3-2F) Two Head / Regressed (NMRT3-2R) Three Head / Flat (NMRT3-3F) Three Head / Regressed (NMRT3-3R)
Lumens / Wattage (Part Numbers)	900lm / 16W (L09) 1500lm / 18W (L15) 2500lm / 27W (L25)	900lm / 11W (L1) 1500lm / 16W (L2) 2500lm / 26W (L3) 3000lm / 32W (L4) 3500lm / 38W (L5)
Color Temperature (Part Numbers)	2700K (27) 3000K (30) 3500K (35) 4000K (40)	
Beam Spread (Part Numbers)	Spot (S) Narrow Flood (M) Flood (F)	Spot (S) Narrow Flood (N) Flood (F)
Finishes (Part Numbers)	Black / White (BW) Silver / Silver (SS) White / White (WW)	