

NTLE-864

4' Track Pack with (3 or 4) MAX Mini LED Track Heads

Source: 13W LED per head

Up to 1000lm per head

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

The track pack comes complete and ready to install with mounting hardware and track heads. Components include (1) 4' single circuit track, (2) end caps, (1) floating canopy feed, and (3 or 4) MAX Mini LED track heads. The practical style fits almost any design criteria.

FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- Black or White finish
- Up to 1000lm / 13W LED output per head
- 2700K, 3000K, 3500K or 4000K @ 90 CRI
- Dimmable
- Easily to longer lengths or additional track heads
- 5-Year Limited Warranty

CONSTRUCTION

Housing: Die-cast aluminum construction dissipates heat for longer life.

Adjustability: 359° horizontal and 90° vertical adjustment

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage Per Head: Up to 1000lm / 13W

Color Temperature: 2700K 3000K, 3500K or 4000K

Color Rendering Index: 90+ CRI

Beam Spread: 41° Narrow Flood

Lifetime: 50,000 hours @ L70

Dimming: Triac or ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

One / Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

LABELS AND LISTINGS

- cETLus Listed for dry locations
- [5-Year Limited Warranty](#)
- FCC compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2019



Performance Data Per Head

Part Number	Lumens	CCT
NTLE-864927	958lm	2700K
NTLE-864930	976lm	3000K
NTLE-864935	985lm	3500K
NTLE-864940	1006lm	4000K

Delivered lumens will vary depending on finish

PRODUCT IMAGES



NTLE-864B



NTLE-864W

4' Track Pack with (3 or 4) MAX Mini LED Track Heads

Color Temperature	Finish	Number of Track Heads
NTLE-864927N = 2700K	B = Black	(blank) = Three Track Heads
NTLE-864930N = 3000K	S = Silver	/4H = Four Track Heads
NTLE-864935N = 3500K	W = White	
NTLE-864940N = 4000K		

Example: **NTLE-864935NB** = 4' Track Pack with (3) MAX Mini LED Track Heads, 3500K / 90 CRI, Black Finish


PHOTOMETRICS

MAC XL LED Track Head

Type _____
 Project _____
 Catalog No. _____
 Notes _____

Test Information

Test Number: NTR11020
 Part Number: NTE-875L940X18W
 Beam Spread: 25° Spot
 Lumens: 1252lm
 Wattage: 17W
 Efficacy: 73lpw
 CCT / CRI: 4000K / 90 CRI
 Spacing Criteria (0°-180°): 0.44
 Spacing Criteria (90°-270°): 0.44



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	279fc	1'-10"
6'	124fc	2'-8"
8'	69.7fc	3'-7"
10'	44.6fc	4'-6"
12'	31fc	5'-5"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	1031	82.4
0-40	1127	90
0-60	1214	97
0-90	1242	99.2
90-180	9	0.8
0-180	1252	100

Candela Table

Vertical Angles	Candela
0	4460
5	4037
15	1633
25	476
35	146
45	68

Test Information

Test Number: NTR11021
 Part Number: NTE-875L940X18W
 Beam Spread: 48° Flood
 Lumens: 1251lm
 Wattage: 17.48W
 Efficacy: 72lpw
 CCT / CRI: 4000K / 90 CRI
 Spacing Criteria (0°-180°): 0.76
 Spacing Criteria (90°-270°): 0.76



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	105fc	3'-6"
6'	46.7fc	5'-4"
8'	26.2fc	7'
10'	16.8fc	8'-10"
12'	11.7fc	10'-7"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	862	68.9
0-40	1067	85.3
0-60	1209	96.6
0-90	1246	99.6
90-180	5	0.4
0-180	1251	100

Candela Table

Vertical Angles	Candela
0	1680
5	1636
15	1306
25	769
35	321
45	124

Lumen Output Multipliers

Color Temperature: 2700K (0.84), 3000K (0.95), 4000K (1.00)