

24V COB TAPE LIGHT

High Output • 450 lumens per foot Standard Output • 210 lumens per foot

COB LED Tape light creates an uniform seamless line of light, without the need for additional diffused covers or accessories. Producing up to 450 lumens per foot in dedicated color temperatures, tape light is a perfect solution for low clearance or reflective surfaces to eliminate all glare or dotting.

FEATURES

- · 24V system requires class 2 LED driver
- · Dimmable with dimmable power supply
- · Seamless COB eliminates LED dotting
- · Delivering 450lm/4.5W or 210lm/2.4W per foot
- · Dedicated color temperatures (2700K, 3000K, 3500K or 4000K)
- · Cuttable every 1.79" and connectable with accessories
- · Easy installation with 3M™ adhesive pre-installed
- · cULus listed for indoor dry location (IP20 rated)
- · Rolls include a 12" power cord and mounting clips
- · Range of mounting accessories, drivers and connectors
- · 5-year limited warranty



PART NUMBER



24V COB LED TAPE LIGHT

NUTP14 = 450lm / 4.5W per foot





NUTP15 = 2101m / 2.4W per foot	CUB24CVIUU = IUU ROII	-930 = 3000K -935 = 3500K -940 = 4000K		
TAPE LIGHT ACCESSORIES				
PART NUMBER	DESCRIPTION			
NATLCB-708 NATLCB-708/BC	12" Hardwire Power Cord 6" Power Cord with DC Connector			
NATLCB-TB NATLCB-TB/60 NATLCB-TB707	Terminal Block for Cord (not included) Terminal Block with 60" Cord (included) Terminal Block for Tape to Tape			
NATLCB-707	End to End Connector			
NATLCB-703 NATLCB-706 NATLCB-718 NATLCB-736 NATLCB-772	3" Linking Cable 6" Linking Cable 18" Linking Cable 36" Linking Cable 72" Linking Cable			

"L" Connector
"T" Connector


"X" Connector


LENGTH

COB24CV16 = 16.4' Roll

CCT

-927 = 2700K








NATLCB-L

NATLCB-T NATLCB-X



COB LED Tape Light

Actual Size



24V COB LED TAPE LIGHT ССТ PART NUMBER LENGTH **NUTP14** = 450lm / 4.5W per foot **COB24CV16** = 16.4' Roll **-927** = 2700K **NUTP15** = 210lm / 2.4W per foot COB24CV100 = 100' Roll **-930** = 3000K **-935** = 3500K **-940** = 4000K

Input Voltage: 24VDC Included: 12" Power Cord

Accessories & Connectors





NATLCB-707 End to End Connector

Width: 0.39"

Cuttable every 1.79"



NATLCB-L "L" Connector

ACCESSORIES & CONNECTORS			
PART NUMBER	DESCRIPTION		
NATLCB-708	12" Hardwire Power Cord		
NATLCB-708/BC	6" Power Cord with DC Connector		
NATLCB-TB	Terminal Block for Cord (not included)		
NATLCB-TB/60	Terminal Block with 60" Cord (included)		
NATLCB-TB707	Terminal Block for Tape-to-Tape		
NATLCB-707	End to End Connector		
NATLCB-703	3" Linking Cable		
NATLCB-706	6" Linking Cable		
NATLCB-718	18" Linking Cable		
NATLCB-736	36" Linking Cable		
NATLCB-772	72" Linking Cable		
NATLCB-L	"L" Connector		
NATLCB-T	"T" Connector		
NATLCB-X	"X" Connector		



NATLCB-T "T" Connector



NATLCB-X "X" Connector

Mounting Options


NATLCB-TB707

Terminal Block with Tape to Tape

NATLCB-TB/60

Terminal Block with 60" Cord







NATL2-C24A 4' Shallow Channel



NATL2-C25A 4' Deep Recessed Channel



NATL2-C26A 4' Deep Channel



NATL2-C29W 4' Trimless Channel

1	1
	4
4	

NATLCB-709

(15) Clear Mounting Clips (Pack of 32 are included with roll)

MOUNTING OPTIONS		
PART NUMBER	DESCRIPTION	FINISH
NATLCB-709	Clear Mounting Clips (Pack of 15)	Clear
NATL2-C23A NATL2-C24A NATL2-C25A NATL2-C26A	4' Shallow Recessed Channel 4' Shallow Channel 4' Deep Recessed Channel 4' Deep Channel	Aluminum
NATL2-C29W	4' Trimless Channel	White

WWW.NORALIGHTING.COM ML-COBTF1124