NPTCBSW-22

2' x 2' LED Troffer with Selectable Lumens & CCT

Source: 18W to 38W LED 2250lm to 4600lm

AVAILABLE JANUARY 2026

Туре	
Project	
Catalog No.	
Notes	

PRODUCT DESCRIPTION

LED troffers provide both functionality and efficiency with two integrated, selectable switches. Selectable lumens allow for a variety of mounting heights, and Selectable CCT adjusts the color temperature. A smooth matte white finish provides glarereducing general lighting for commercial and industrial applications. The luminaires are suitable for office, school, retail, hospital, and hospitality applications.

FEATURES

- · Selectable Lumen switch changes the wattage
- · Selectable Color Temperature switch changes the CCT (30K / 35K / 40K / 50K / 65K)
- · 0-10V dimming
- · Optional remote emergency
- · DLC Listed

SPECIFICATION

Housing: Die form steel powder coated in matte white reflective surface for soft uniform reflectance. Enclosed driver compartment is easily accessible from below via a hinged LED platform. Built in earthquake clips.

Lens: Polycarbonate diffused white lens evenly distributes light and maximizes performance. Diffused lens reduces glare and offers more balanced lighting, eliminating shadowy cave effects caused by parabolics.

Optics: Polycarbonate diffused white lens evenly distributes light and maximizes performance.

Installation: The luminaire fits into standard 15/16" and narrow 9/16" T-grid ceiling systems. Optional surface mount kits and recessed mounting kits are also available.

ELECTRICAL

Input Voltage: 120-277VAC 60Hz Lumens / Wattage: See chart below

Color Temperature: Selectable CCT (3000K / 3500K / 4000K / 5000K / 6500K); Preset to 3000K

Color Rendering Index: 85 CRI Operating Temperatre: 0°-40°C **Dimming:** 0-10V dimming down to 10%

Click Here or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

Emergency: Luminaires are compatible with remote emergency kit. Each kit includes a 20W driver, junction box and remote test switch (NPTCBSW-EMKIT). Battery operates luminaire at 7W for 90 minute emergency operation on fully charged battery.

LABELS AND LISTINGS

- · cETLus Listed for Damp Locations
- · 5-Year Limited Warranty
- · DLC Listed
- · FCC certified







Size	2' x 2'
Lumen Output	2250lm / 3500lm / 4600lm
Selectable Wattage	18W / 28W / 38W

Notes: Lumens shown at 5000K and will vary depending on CCT

PRODUCT IMAGES AND DIMENSIONS










Three position sliding switch

Five position sliding switch 30K / 35K / 40K / 50K / 65K



NPTCBSW-22/SCW 2' x 2' LED Troffer

2' x 2' LED Troffer with Selectable Lumens & CCT

Description

NPTCBSW-22/SCW = 2' x 2' LED Troffer

* PACKAGED AND SOLD IN MULTIPLES OF TWO

Optional Accessories

Description

NPDBL-22DDFK/W = Surface Mounting Kit for 2' x 2' Troffer NPDBL-22RFK/W = Recessed Mounting Kit for 2' x 2' Troffer NPTCBSW-EMKIT = 20W Emergency Driver Kit w/ Remote Test Switch

Example: NPTCBSW-22/SCW = 2' x 2' LED Troffer with Selectable Lumens & CCT, White Finish

