

NTLE-865

4' Track Pack with (3 or 4) MAX LED Track Heads

Source: 25W LED per head
Up to 2450lm per head

PRODUCT DESCRIPTION

The track pack comes complete and ready to install with mounting hardware and track heads. Components include (1) 4' single circuit track, (2) end caps, (1) floating canopy feed, and (3 or 4) MAX LED track heads. The practical style fits almost any design criteria.

FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- Black or White finish
- Up to 2450lm / 25W LED output per head
- 2700K, 3000K, 3500K or 4000K @ 90 CRI
- Dimmable
- Easily to longer lengths or additional track heads
- 5-Year Limited Warranty

CONSTRUCTION

Housing: Die-cast aluminum construction dissipates heat for longer life.

Adjustability: 359° horizontal and 90° vertical adjustment

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage Per Head: Up to 2450lm / 25W

Color Temperature: 2700K 3000K, 3500K or 4000K

Color Rendering Index: 90+ CRI

Beam Spread: 20° Spot, 32° Narrow Flood, 54° Flood

Lifetime: 50,000 hours @ L70

Dimming: Triac or ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

One / Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

LABELS AND LISTINGS

- cETLus Listed for dry locations
- [5-Year Limited Warranty](#)
- FCC compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2025



Type

Project

Catalog No.

Notes

Performance Data Per Head		
Part Number	Lumens	CCT
NTLE-865927	2100lm	2700K
NTLE-865930	2271lm	3000K
NTLE-865940	2466lm	4000K
Delivered lumens will vary depending on finish		

PRODUCT IMAGES



NTLE-865B



NTLE-865W

4' Track Pack with (3 or 4) MAX LED Track Heads

Color Temperature	Beam Spread	Finish	Number of Track Heads
NTLE-865927 = 2700K	S = 20° Spot	B = Black	(blank) = Three Track Heads
NTLE-865930 = 3000K	N = 32° Narrow Flood	W = White	/4H = Four Track Heads
NTLE-865935 = 3500K	F = 54° Flood		
NTLE-865940 = 4000K			

Example: NTLE-865935NB = 4' Track Pack with (3) MAX LED Track Heads, 3500K, Narrow Flood Optic, Black Finish

PHOTOMETRICS

4' Track Pack with (3 or 4) MAX LED Track Heads

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTT1077R1
Part Number: NTLE-865940SB
Beam Spread: 20° Spot
Lumens: 2156lm
Wattage: 27.89W
Efficacy: 77lpw
CCT / CRI: 4000K / 90 CRI
Spacing Criteria (0°-180°): 0.36
Spacing Criteria (90°-270°): 0.36



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
12'	98fc	4'-4"
14'	72fc	5'
16'	55.1fc	5'-8"
18'	43.6fc	6'-5"
20'	35.3fc	7'-2"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	2001	92.8
0-40	2064	95.7
0-60	2139	99.2
0-90	2156	100
90-180	0	0
0-180	2156	100

Candela Table

Vertical Angles	Candela
0	14117
5	10296
15	3407
25	378
35	86
45	52

Test Information

Test Number: NTT1085R1
Part Number: NTLE-865940NW
Beam Spread: 32° Narrow Flood
Lumens: 2437lm
Wattage: 28.63W
Efficacy: 85lpw
CCT / CRI: 4000K / 90 CRI
Spacing Criteria (0°-180°): 0.54
Spacing Criteria (90°-270°): 0.54



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
12'	47.4fc	6'-10"
14'	34.8fc	8'
16'	26.7fc	9'-1"
18'	21.1fc	10'-4"
20'	17.1fc	11'-5"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	2214	90.8
0-40	2362	96.9
0-60	2422	99.4
0-90	2437	100
90-180	0	0
0-180	2437	100

Candela Table

Vertical Angles	Candela
0	6825
5	6324
15	3707
25	1252
35	157
45	38

Test Information

Test Number: NTT1075R1
Part Number: NTLE-865940FB
Beam Spread: 54° Flood
Lumens: 2466lm
Wattage: 27.88W
Efficacy: 88lpw
CCT / CRI: 4000K / 90 CRI
Spacing Criteria (0°-180°): 0.88
Spacing Criteria (90°-270°): 0.88



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
12'	22.2fc	12'-5"
14'	16.3fc	14'-6"
16'	12.5fc	16'-6"
18'	9.9fc	18'-7"
20'	8fc	20'-8"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	1958	79.4
0-40	2332	94.6
0-60	2454	99.5
0-90	2466	100
90-180	0	0
0-180	2466	100

Candela Table

Vertical Angles	Candela
0	3199
5	3162
15	2810
25	1920
35	568
45	105

Lumen Output Multipliers

Color Temperature: 2700K (0.86), 3000K (0.93), 4000K (1.00)