

RECESSED LIGHTING | CAN-LESS



BASIC INFO	Name	M1	M2	M4	Iolite	M-Wave	M-Curve	FLAT & FLIN	Fire Rated	Theia	Quartz
	Part Number	NM1	NM2	NM4	NIOC	NMW	NMC	NFLAT, NEFLINTW, NFLINA	NFRC	NLTH	NQZ2
	Aperture	1"	2"	4"	1", 2" and 4"	2" and 4"	4" and 6"	4" and 6"	4" and 6"	4", 6" and 8"	4", 6" and 8"
PERFORMANCE	Lumens	100lm or 600lm	400lm to 900lm	950lm or 1100lm	900lm to 1250lm	750lm or 1250lm	900lm or 1300lm	675lm to 1300lm	1200lm to 1550lm	950lm to 2100lm	800lm to 3300lm
	CCT	2700K or 3000K	2700K, 3000K or 4000K	2700K or 3000K	2700K, 3000K, 3500K, 4000K, Comfort Dim	2700K or 3000K	2700K, 3000K, 3500K, 4000K, 5000K	2700K, 3000K, 3500K, 4000K, 5000K	2700K, 3000K, 3500K, 4000K, 5000K	2700K, 3000K, 3500K, 4000K, 5000K	3000K, 3500K, 4000K
	Input Voltage	12V or 120V	120V	120V	120V	120V	120V	120V	120V	120V or 120-277V	120-277V
	Dimming	Triac or ELV	Triac or ELV	Triac or ELV	Triac or ELV	Triac or ELV	Triac or ELV	Triac or ELV	Triac or ELV	Triac, ELV or 0-10V	0-10V
APPEARANCE	Trim Types	Round, Square, Indicator, Louver	Round, Square, Adjustable, Trimless	Round, Square, Adjustable, Elbow	Round, Square, Adjustable, Sloped	Adjustable	Adjustable	Round, Square, Adjustable	Flat or Baffle	Reflector	Round or Square
	Beam Spread	Fixed	Fixed (Elbow includes two)	Fixed (Elbow includes two)	Field Changeable (Three Included)	Field Changeable	Fixed	Fixed	Fixed	Fixed	Fixed
APPLICATION	Rating	IC Airtight	IC Airtight	IC Airtight	IC Airtight	IC Airtight	IC Airtight	IC Airtight	IC Airtight	IC Airtight	IC
	Listing	Wet	Damp or Wet	Damp or Wet	Wet	Wet	Wet	Wet	Wet	Wet	Wet