


RECESSED LIGHTING | DEDICATED



BASIC INFO	Name	Apollo	Iolite	Cobalt	Marquise	Sapphire
	Part Number	NHAP, NAP	NIO	NLCB	NRM3	NC3
	Aperture	3"	1", 2" and 4"	4" and 6"	4", 5" and 6"	4", 6" and 8"
PERFORMANCE	Lumens	800lm to 3000lm	750lm to 1200lm	850lm to 2000lm	900lm to 2500lm	900lm to 5500lm
	CCT	2700K, 3000K, 3500K, 4000K, Comfort Dim	2700K, 3000K, 3500K, 4000K, Comfort Dim	2700K, 3000K, 3500K, 4000K, Comfort Dim	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K
	Input Voltage	120V, 120-277V or 120/277V	120V or 120-277V	120V, 120-277V or 120/277V	120V or 120-277V	120V or 120-277V
	Dimming	Phase, 0-10V, Casambi, DALI, Lutron	Phase, 0-10V, DALI, Lutron	Triac, ELV or 0-10V	Triac, ELV or 0-10V	Triac, ELV or 0-10V
APPEARANCE	Trim Types	Round, Square, Trimless, Adjustable, Wall Wash	Round, Square, Trimless, Adjustable, Wall Wash	Round, Square, Adjustable	Reflector, Baffle, Adjustable, Sloped	Reflector, Adjustable, Wall Wash
	Beam Spread	Fixed or Field Changeable	Field Changeable (Three Included)	Fixed	Spot, Narrow Flood, or Flood	Spot, Narrow Flood, or Flood
APPLICATION	Rating	IC or Non-IC Airtight	IC Airtight	IC or Non-IC Airtight	IC or Non-IC Airtight	Non-IC
	Listing	Damp or Wet	Damp or Wet	Damp or Wet	Damp or Wet	Wet