

RECESSED LIGHTING | RETROFIT



BASIC INFO	Name	Onyx	Cobalt	Pearl	Marquise	Sloped	Sapphire	Quartz
	Part Number	NOX	NLCBC	NPR	NRMC3	NLRS	NCR3	NQZ2
	Aperture	4", 5" and 6"	4", 5" and 6"	4", 5" and 6"	4", 5" and 6"	6"	6" and 8"	4", 6" and 8"
PERFORMANCE	Lumens	700lm to 1350lm	750lm to 1200lm	1200lm	1300lm	1200lm	900lm to 5500lm	Selectable Lumens 800lm to 3300lm
	CCT	2700K, 3000K, 3500K, 4000K, 5000K	2700K, 3000K, 3500K, 4000K, Comfort Dim	2700K, 3000K, 3500K, 4000K, Comfort Dim	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K, 5000K	2700K, 3000K, 3500K, 4000K	Selectable CCT (30K / 35K / 40K)
	Input Voltage	12V or 120V	120V or 120V/277V	12V or 120V	120V	120V	120V or 120-277V	120-277V
	Dimming	Triac or ELV	Triac, ELV or 0-10V	Triac or ELV	Triac or ELV	Triac or ELV	Triac/ELV or 0-10V	0-10V
APPEARANCE	Trim Types	Round, Square, Adjustable, Wall Wash	Round, Square, Adjustable, Elbow	Round, Square, Adjustable, Pinhole	Reflector or Baffle	Reflector or Baffle	Reflector, Wall Wash or Decorative Glass	Round or Square
	Beam Spread	Fixed	Fixed (Adjustable includes two optics)	Field Changeable (Three Included)	Spot, Narrow Flood, or Flood	Fixed	Spot, Narrow Flood, or Flood	Fixed
APPLICATION	Rating	Specified by housing	Specified by housing	Specified by housing	Specified by housing	Specified by housing	Non-IC	IC
	Listing	Damp or Wet	Damp or Wet	Damp or Wet	Damp or Wet	Damp	Wet	Wet