

NTP-713

6" Airtight Polycarbonate Baffle Cone with Flange

Type	
Project	
Catalog No.	
Notes	

CONSTRUCTION

High-quality, UV-resistant polycarbonate baffle designed for coastal environments, featuring a flanged trim and deep grooves to reduce aperture glare.

MOUNTING

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Socket can be mounted directly to trim without bracket.

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

7W PAR20 max. (NHIC-17QAT; NHIC-17QNBAT; NHRIC-17QAT; NHRIC-17QNBAT)
9.5W PAR30S max. (NHIC-17QAT; NHIC-17QNBAT; NHRIC-17QAT; NHRIC-17QNBAT)
15W A19/PAR38 max. (NHIC-17QAT; NHIC-17QNBAT; NHRIC-17QAT; NHRIC-17QNBAT)
20W BR40 max. (NHIC-17QAT; NHIC-17QNBAT; NHRIC-17QAT; NHRIC-17QNBAT)

LISTINGS

cULus Listed for Damp Locations when used with compatible housing





PRODUCT IMAGES & DIMENSIONS



NTP-713B
Black Baffle
Black Flange



NTP-713W
White Baffle
White Flange



6" Airtight Polycarbonate Baffle Cone with Flange

Catalog No.

NTP-713B = Black Baffle / Black Flange
NTP-713W = White Baffle / White Flange

Compatible Housings

Catalog No.

NHIC-17QAT = 6" IC Airtight New Construction
NHIC-17QNBAT = 6" IC Airtight New Construction; No Bracket
NHRIC-17QAT = 6" IC Airtight Remodel
NHRIC-17QNBAT = 6" IC Airtight Remodel; No Bracket

Example: NTP-713W = 6" Airtight Polycarbonate Baffle Cone with Flange, White Baffle / White Flange